

ZEETEX TURBO DIESEL ENGINE OIL

SAE GRADE: 15W/40, 20W/50

PERFORMANCE LEVEL:

API classification: CF-4/SJ

European specification: ACEA A2/B2/E2/98 MB 227.1,228.1, VOLVO VDS

U.S. Military specification: MIL-L-2104 E, MIL-L-46152 E

- ZEETEX TURBO DIESEL ENGINE OIL is a supreme quality multigrade diesel engine oil designed for all types of naturally aspirated and turbo charged diesel engines, operating under high speed, high load and severe field conditions.
- ZEETEX TURBO DIESEL ENGINE OIL is designed for extended oil drain intervals, in diesel powered on and off road equipment. It has outstanding detergency and dispersancy levels and provides excellent protection from oxidation, rust and corrosion. The multigrade formulation provides optimum fuel economy, oil consumption control, low temperature pumpability and startability.

PHYSICAL CHARACTERISTICS	TEST METHOD	SAE GRADE/TYPICAL VALUE	
		15W/40	20W/50
Specific Gravity @ 60/60 °F	ASTM D-4052	0.885	0.892
Viscosity Kinematic, cSt @ 40 °C	ASTM D-445	114	158
Viscosity Kinematic, cSt @ 100 °C	ASTM D-445	15.0	18.5
Viscosity Index	ASTM D-2270	136	126
Flash Point, COC, °C	ASTM D-92	220	230
Pour Point °C	ASTM D-97	-27	-24
TBN, mg KOH/g	ASTM D-2896	11	11
Sulphated Ash, %wt	ASTM D-874	1.4	1.4