

# ZEETEX THUNDER 3000 ENGINE OIL

SAE GRADE: 30,40,50

PERFORMANCE LEVEL:

API classification: CC/SC

U.S. Military specification: MIL-L-2104B

- ZEETEX THUNDER 3000 ENGINE OIL is a good quality mono grade engine oil which meets and exceeds the requirement of API CC/SC. It is a blend of high viscosity index base oil and balanced additive package.
- ZEETEX THUNDER 3000 ENGINE OIL has an excellent detergent – dispersant package to control sludge formation which prevents formation of hard carbon deposits and lacquer formation when engine is operating at its peak. It has anti-wear, anti-rust and corrosion inhibitors which protect the engine against rapid degradation in severe operating conditions.
- ZEETEX THUNDER 3000 ENGINE OIL is recommended for passenger cars, light-duty trucks and vans operating on diesel/gasoline fuels.

PHYSICAL CHARACTERISTICS	TEST METHOD	SAE GRADE/TYPICAL VALUE		
		30	40	50
Specific Gravity @ 60/60 °F	ASTM D-4052	0.885	0.889	0.900
Viscosity Kinematic, cSt @ 40 °C	ASTM D-445	102	158	208
Viscosity Kinematic, cSt @ 100 °C	ASTM D-445	11.5	15.5	18.5
Viscosity Index	ASTM D-2270	99	99	98
Flash Point, COC, °C	ASTM D-92	230	240	250
Pour Point °C	ASTM D-97	-9	-6	-6
TBN, mg KOH/g	ASTM D-2896	3.50	3.50	3.50
Sulphated Ash, %wt	ASTM D-874	0.48	0.48	0.48