

ZEETEX GEAR OIL

SAE GRADE: 90, 140

API classification GL-1

U.S. Military specification: MIL-L-2104B

- ZEETEX GEAR OIL is a high quality straight mineral lubricant for lightly loaded manual transmission and spiral bevel, rear axle assemblies and worm gear drives. It can be used in enclosed gear boxes of any equipment where manufacture permits use of API GL 1 level oil.
- ZEETEX GEAR OIL is a blend of natural high VI solvent refined paraffinic base stock and excellent anti-foam additive package. It maintains its viscosity during light operating parameters. It has good resistance to oxidation, rust and corrosion and has good demulsibility.

| PHYSICAL CHARACTERISTICS | TEST METHOD | SAE GRADE/TYPICAL VALUE | |
|-----------------------------------|-------------|-------------------------|-------|
| | | 90 | 140 |
| Specific Gravity @ 60/60 °F | ASTM D-4052 | 0.886 | 0.905 |
| Viscosity Kinematic, cSt @ 40 °C | ASTM D-445 | 178 | 460 |
| Viscosity Kinematic, cSt @ 100 °C | ASTM D-445 | 18 | 29 |
| Viscosity Index | ASTM D-2270 | 96 | 96 |
| Flash Point, COC, °C | ASTM D-92 | 240 | 290 |
| Pour Point °C | ASTM D-97 | -6 | -6 |